

FARMI FOREST

The pioneer in **smart** forestry

CHIPPERS



CH10



Application	Landscaping	Discharge pipe	Manual/to two
Output (m3/h)	1-3	turning	sides
Thickness of chip (mm)	12	Smart feed electrics	No
Max log diameter (mm)	100	Power source	Tractor
Power demand (kW)	7.5-30	Feed	Manual
Speed of rotation (rpm)	540/1000	Hydraulic cover	No
Number of knives (pcs)	2	opening	
Chipper weight (kg)	193/210	Hydraulic discharge	No
Rotor diameter (mm)	550	pipe steering	
Rotor weight (kg)	46	Crane mounting	No
3-point mounting	Standard	Remote control	No
Discharge pipe reach, short/long (m)	1.5	Feeder	Dropdown chute

CH18



Application	Landscaping	Discharge pipe	Manual/to two
Output (m3/h)	5-15	turning	sides
Thickness of chip (mm)	10	Smart feed electrics	Standard
Max log diameter (mm)	180	Power source	Tractor
Power demand (kW)	30-70	Feed	Manual
Speed of rotation (rpm)	540/1000	Hydraulic cover	No
Number of knives (pcs)	4	opening	
Chipper weight (kg)	400	Hydraulic discharge	No
Rotor diameter (mm)	670	pipe steering	
Rotor weight (kg)	55	Crane mounting	No
3-point mounting	Standard	Remote control	No
Discharge pipe reach, short/long (m)	2.2/2.9	Feeder	Roller feeder

CH27 DMR



Application	Bioenergy	Discharge pipe	Manual/360
Output (m3/h)	5-25	turning	degrees
Thickness of chip (mm)	5-25	Smart feed electrics	Standard
Max log diameter (mm)	250	Power source	Tractor
Power demand (kW)	40-115	Feed	Manual
Speed of rotation (rpm)	540/1000	Hydraulic cover	Optional
Number of knives (pcs)	2	opening	
Chipper weight (kg)	1180	Hydraulic discharge	Optional
Rotor diameter (mm)	1036	pipe steering	
Rotor weight (kg)	240	Crane mounting	No
3-point mounting	Standard	Remote control	No
Discharge pipe reach, short/long (m)	3/3.9	Feeder	Roller feeder

Farmi chippers have been designed with ease of use, productivity and, of course, safety in mind.

Our extensive wood chipper range includes models that meet the demands for both bioenergy and landscaping applications.

CH27 ACR



Application	Bioenergy	Discharge pipe	Manual/360
Output (m3/h)	10-60	turning	
Thickness of chip (mm)	5-25	Smart feed electrics	Standard
Max log diameter (mm)	270	Power source	Tractor
Power demand (kW)	40-115	Feed	Crane
Speed of rotation (rpm)	540/1000	Hydraulic cover	Optional
Number of knives (pcs)	2	opening	
Chipper weight (kg)	1250	Hydraulic discharge	Optional
Rotor diameter (mm)	1036	pipe steering	
Rotor weight (kg)	240	Crane mounting	Yes
3-point mounting	Standard	Remote control	Optional
Discharge pipe reach, short/long (m)	3/3.9	Feeder	Roller feeder

CH27 ACC



Application	Bioenergy	Discharge pipe	Manual/360
Output (m3/h)	10-70	turning	
Thickness of chip (mm)	5-25	Smart feed electrics	Standard
Max log diameter (mm)	270	Power source	Tractor
Power demand (kW)	40-115	Feed	Crane
Speed of rotation (rpm)	540/1000	Hydraulic cover	Optional
Number of knives (pcs)	2	opening	
Chipper weight (kg)	1450	Hydraulic discharge	Optional
Rotor diameter (mm)	1036	pipe steering	
Rotor weight (kg)	240	Crane mounting	Yes
3-point mounting	Standard	Remote control	Optional
Discharge pipe reach, short/long (m)	3/3.9	Feeder	Conveyor feeder

CH38



Application	Bioenergy	Discharge pipe	Hydraulic/300
Output (m3/h)	30-100	turning	
Thickness of chip (mm)	10-30	Smart feed electrics	Standard
Max log diameter (mm)	380	Power source	Tractor
Power demand (kW)	125-205	Feed	Crane
Speed of rotation (rpm)	540/540E/1000	Hydraulic cover	Standard
Number of knives (pcs)	4	opening	
Chipper weight (kg)	2450	Hydraulic discharge	Standard
Rotor diameter (mm)	1460	pipe steering	
Rotor weight (kg)	600	Crane mounting	Yes
3-point mounting	Standard	Remote control	Optional
Discharge pipe reach, short/long (m)	4.1	Feeder	Conveyor feeder



FARMI FOREST
The pioneer in **smart** forestry



FARMI FOREST

The pioneer in **smart** forestry

Distributed by :



Telephone: 418 839-4127
Toll Free: 1 866 718-4746
Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca